

**Amendments to the Claims**

The following listing of claims replaces all prior versions and listings of claims in this application:

**Listing of Claims**

- 1-7. (Canceled)
8. (Previously presented) The device of claim 29, wherein the mounting base is of unitary construction.
9. (Original) The device of claim 8, wherein  
the left wing section is connected with the intermediate section by a first transition step;  
the right wing section is connected with the intermediate section by a second transition step;  
the center section is connected with the intermediate section along a first edge by a third transition step; and  
the center section is connected with the intermediate section along a second edge by a fourth transition step.
10. (Original) The device of claim 8, wherein  
the intermediate section further comprises a left flange and a right flange;  
the center section defines a window opening, wherein  
a first portion of the center section extends above the window opening, and  
a second portion of the center section extends below the window opening; and  
wherein  
the left flange and the right flange extend behind the window opening to meet at a seam.
11. (Previously presented) The device of claim 29, wherein the slot is defined by the space between the center section and the intermediate section.
12. (Withdrawn) The device of claim 29 further comprising a retention panel connected with the intermediate section and positioned opposite the center section, wherein the slot is further defined by the retention panel.

13. (Withdrawn) The device of claim 32, wherein the sliding member is curved about a longitudinal axis to define a convex surface on a rear side of the sliding member.

14. (Withdrawn) The device of claim 13 further comprising an elastic member, wherein the elastic member is attached at a first end to the sliding member;  
the elastic member is attached at a second end to the mounting base; and  
the elastic member is substantially housed within boundaries defined by the convex surface of the sliding member.

15. (Canceled)

16. (Withdrawn) The device of claim 29 further comprising  
a retention panel connected with the intermediate section and positioned opposite the center section, wherein the slot is further defined by the retention panel; and  
an elastic member; wherein  
the sliding member is curved about a longitudinal axis to define a convex surface on a rear side of the sliding member;  
the elastic member is attached at a first end to the sliding member;  
the elastic member is attached at a second end to the retention panel; and  
the elastic member is substantially housed within boundaries defined by the convex surface of the sliding member.

17. (Previously presented) The device of claim 32, wherein the first retainer clip, the second retainer clip, and third retainer clip each further comprise  
a corresponding shelf; and  
a corresponding lip, wherein  
each corresponding shelf is connected with and generally orthogonal to the right wing section, the left wing section, and the sliding member, respectively; and  
each corresponding lip is connected with and generally orthogonal to the respective corresponding shelf.

18. (Previously presented) The device of claim 32, wherein the first retainer clip is oriented at a first angle with respect to an orientation of the third retainer clip and the second retainer clip is oriented at a second angle with respect to the orientation of the third retainer clip.

19. (Original) The device of claim 18, wherein the first angle is equal and opposite to the second angle.

20. (Previously presented) The device of claim 32, wherein the sliding member further comprises a retention member, and wherein

the third retainer clip is disposed on a first end of the sliding member;

the retention member is disposed on a second end of the sliding member; and

the retention member is adapted to engage the mounting base to arrest the travel of the sliding member within the slot.

21. (Previously presented) The device of claim 32, wherein the device is composed of a metal or metal alloy selected from the group consisting of: aluminum, stainless steel, copper, nickel, tin, titanium, and brass.

22. (Previously presented) The device of claim 32, wherein the device is composed of a plastic or composite material.

23. (Canceled)

24. (Withdrawn) The device of claim 32, wherein at least one of the sliding member, the left wing section, and the right wing section is adapted to extend telescopically.

25-28. (Canceled)

29. (Previously presented) A device for holding a cooking container lid, the device comprising

a mounting base having

a center section, wherein the center section defines a slot;

a left wing section connected with the center section, wherein

the left wing section further comprises a first retainer clip;

a right wing section connected with the center section, wherein  
the right wing section further comprises a second retainer clip; and  
an intermediate section disposed between the center section and each of the left  
wing section and the right wing section, wherein  
the center section is contained within a first plane;  
the intermediate section is contained within a second plane;  
the left wing section and the right wing section are both contained  
within a third plane;  
the first plane, the second plane, and the third plane are parallel to  
each other;  
the first plane is spaced apart from the second plane;  
the second plane is spaced apart from the third plane; and  
the first plane is spaced apart from the third plane; and  
an elongate sliding member, wherein  
the sliding member further comprises a third retainer clip; and  
the sliding member both travels within and is retained within the slot.

30 and 31. (Canceled)

32. (Previously presented) A device for holding a cooking container lid, the device  
comprising

a mounting base having  
a center section, wherein the center section defines a slot;  
a left wing section connected with the center section, wherein  
the left wing section further comprises a first retainer clip; and  
a right wing section connected with the center section, wherein  
the right wing section further comprises a second retainer clip; and  
an elongate sliding member, wherein  
the sliding member further comprises a third retainer clip; and  
the sliding member both travels within and is retained within the slot; and  
wherein

the center section is spaced apart from both the left wing section and the right wing section;

the center section is connected with the left wing section along a first edge by a first transition step; and

the center section is connected with the right wing section along a second edge by a second transition step; and

wherein the left wing section and the right wing section each define a mounting aperture.